Product Data Sheet (For Indian Customers)



Data Sheet No: MAL 1708

Issue date: 10 Aug 2017

DL- MALIC ACID - FOOD GRADE

 $\begin{array}{lll} \text{Chemical Formula} & : C_4 H_6 O_5 \\ \text{Molecular weight} & : 134.09 \\ \text{CAS Registry Number} & : 6915-15-7 \\ \end{array}$

E. Number : 296 Molecular Structure :

HO OH OH

Appearance: White Crystalline Granular / Fine Granular / Powder

Description: DL-Malic Acid is an important organic compound having a sharp, clean, tart, acidic taste. It is free flowing, stable and

hygroscopic.

Reach Registration Number:

01-2119552463-40-0000

License under Food Safety and Standards Act, 2006 Number: 10012042000166

U.S.FDA Registration Number:

13392034936

Grades of Granularity:

Granular:

100% passing through USS 10 mesh 10% max. passing through USS 50 mesh

Fine Granular:

99% Min. passing through USS 25 mesh 5% Max. Passing through USS 100 mesh

Powder:

75% Min. passing through USS 50 mesh

SPECIFICATIONS (Conform to FCC 10):

Characteristics	Unit	Guaranteed		Typical
Assay on dry basis (Titrimetry)	Wt. %	Min	99.5	99.8
Maleic acid	Wt. %	Max	0.05	0.03
Fumaric acid	Wt. %	Max	1.0	0.6
Residue on Ignition (sulfated Ash)	Wt. %	Max	0.05	0.02
Optical (Specific) Rotation	$[\alpha]_{\mathrm{D}}^{2.5^{\circ}}$	Between	- 0.10 and + 0.10	- 0.10 and + 0.10
Lead (as Pb)	PPM	Max	2	<2
Water Insoluble Matter	Wt. %	Max	0.1	0.02

ADDITIONAL SPECIFICATIONS (TYPE):

Characteristics	Unit	Guaranteed		Typical
Moisture (by Loss on Drying)	Wt. %	Max	0.3	0.2
Heavy metals (as Pb)	PPM	Max	5	<5
Arsenic (as As)	PPM	Max	1	<1
Mercury (as Hg)	PPM	Max	1	<1
Zinc	PPM	Max	50	<0.3 *
Cadmium (as Cd)	PPM	Max	1.5	<1
Copper	PPM	Max	30	<0.1 *
Tin	PPM	Max	250	<6.0 *

Note1: On request. & Note2: * means Detection Limits.

TYPICAL PACKAGING:

- 1.PE lined, PE laminated HDPE bag 25 Kg
- 2.PP laminated 4 ply Paper Bag 25 Kg
- 3. Fibre drum with PE liner 30 Kg
- 4.1 Kg pouches in 25 Kg HDPE bag

Legislation:

Thirumalai Chemicals' DL-Malic Acid meets the Food Chemical Codex and European pharmacopoeia specifications. German Food additive purity regulation, allows DL-Malic Acid to be added to all food products, without any quantitative limit.

In UK DL-Malic Acid is approved for use by the following:

- 1. The food standards (Preserves) order 1953
- 2. The Soft drinks regulation 1964, amended 1995
- 3. Miscellaneous additive in Food regulation 1980 No.1834 for general use for an acidulant.

United States, Food and Drug Administration has approved the use of DL-Malic Acid as a general-purpose food additive, except in Baby Foods. It is included in the FDA list as a Generally Recognized as Safe (GRAS) substance.

In India, DL-Malic acid has been approved for use in carbonated beverages and as an acidulant in miscellaneous foods by - Food Safety and Standards Act -2006

Uses:

- DL-Malic Acid, the natural acid constituent of apple, finds wide application in the food industry. Due to its compatibility with all types of flavour, the flavour enhancing property, the sharp, lingering acid taste and the high water solubility nature, it is ideally suited for the preparation of Juices, Soft drinks, Cider and Wines. Its' non-hygroscopic, free flowing nature, makes it the preferred acid for dry squash juice mixes.
- When used in sugar confectionery, the low melting point of DL-Malic Acid gives greater clarity to the finished product. In cheese preparation, it increases the product yield.
- DL-Malic Acid is used in paneer preparation
- In diet products, it suppresses the bitter after taste of artificial sweeteners and reduces the amount needed, without affecting the sweetness.
- In fruit and vegetable canning, DL-Malic Acid is used for pH adjustment.
- In the edible oil processing/refining it is used to remove and control traces of metal impurities and as a synergist in admixture with antioxidants, to control rancidity.
- DL-Malic Acid is also used in Pharmaceuticals, Cosmetics, Metal cleaning and Textile finishing.

Storage:

It must be stored in ambient temperature, properly covered in a dry well ventilated place.
Shelf Life: 24 months from the date of production under recommended storage conditions.

For further details please contact Thirumalai Chemicals Limited

Factory:

25-A, Sipcot Industrial Complex Ranipet - 632 403 Tamil Nadu, India.

Phone: +91-4172-244441 /2/6/8

Fax : +91-4172-244308 e-mail:

nair.pmc@thirumalaichemicals.com

Contact: Mr. P.M.C.Nair

Mumbai Office: (Sales & Business)

"Thirumalai House" Plot No.101-102, Road No.29, Sion (East)

Mumbai-400 022, Maharashtra, India.

Phone :+91-22-43686200

Fax : +91-22-2401-1699 / 7869

e-mail:

foodingredients@thirumalaichemicals

.com

Chennai Office: (Sales & Business)

SPIC HOUSE, 5th Floor, No.88, Mount Road, Guindy, Chennai - 600 032

Tamil Nadu, India. Phone:+91-44-66057700

e-mail:

joseph.r@thirumalaichemicals.com

Contact: Mr. S. Venkatraghavan Mr. Joseph Rajkumar

Website: http://www.thirumalaichemicals.com

The present product data sheet has the purpose of inform the clients on the quality of our product. The data herein is based on our present best knowledge. For a better suitability of the product for your particular purpose, tests are recommended prior product use. Our clients must be sure that the present data sheet hasn't been changed or replaced by a newer edition.